

N, N4

End-Suction Centrifugal Pumps standardized EN 733



The electropumps N, B-N, N4, B-N4 series comply with the European Regulation no. 547/2012.

Materials

Components	N, N4 Mechanical seal	N, N4 Stuffing box	B-N, B-N4 Mechanical seal
Pump casing	Cast iron		Bronze
Casing cover	GJL 200 EN 1561		G-Cu Sn 10 EN 1982
Impeller	Cast iron		Bronze
	GJL 200 EN 1561		G-Cu Sn 10 EN 1982
	Brass P- Cu Zn 40 Pb 2 UNI 5705 For 32-125, 32-160, 32-200, 40-200		
Shaft	Chrome steel 1.4104 EN 10088 (AISI 430)	Carbon steel C 40 UNI 7845	Cr-Ni-Mo steel 1.4401 EN 10088 (AISI 316)
Shaft sleeve	—	Bronze G-Cu Sn5 Zn5 Pb5 EN 1982 with chromate surface	—
Mechanical seal	Carbon - Ceramic - NBR	—	Carbon - Ceramic - NBR
Counter-flanges	Steel Fe 430B UNI 7070		

Construction

Single-stage end-suction centrifugal pumps, with bearing bracket.

Nominal duty points and main dimensions in accordance with EN 733. Back Pull-Out construction, for simple and quick dismantling and reassembly.

N, N4: version with pump casing and lantern bracket in cast iron.
B-N, B-N4: version with pump casing and lantern bracket in bronze.
(the pumps are supplied fully painted).

Rated speed of rotation (50 Hz): **N** ≈ 2900 rpm.
N4 ≈ 1450 rpm.

Connections: PN 10 flanges EN 1092-2.

Counter-flanges (on request)

Sizes	Flanges
from 32-160 to 50-250	Screwed flanges PN 16 EN 1092-1
from 65-125 to 150-400	Flanges for welding PN 10 EN 1092-1

Shaft sealing

- Standardized mechanical seal in accordance with ISO 3069.
- Stuffing box seal (on request).

Applications

For clean liquids, without abrasives, which are non-aggressive for the pump materials (contents of solids up to 0.2%).

For water supply.

For heating, air conditioning, cooling and circulation plants.

For civil and industrial applications and for agriculture.

For fire fighting applications.

For irrigation.

Operating conditions

Liquid temperature from -10 °C to +90 °C.

Ambient temperature up to 40 °C.

Total suction lift up to 7 m.

Maximum permissible working pressure up to 10 bar (16 bar for N,N4 65/125, N,N4 65/160 and N,N4 80/160).

Maximum permissible rotation speed: see table on page 70.

Pump-Motor unit

N,N4 pump connected to a standard electric motor in B3 construction form (EN 60072-1), by means of a baseplate, driven by a flexible coupling and with coupling protection.

Three-phase 400 V , 50 Hz

Classification scheme IE2 for three-phase motors from 0,75 kW to 5,5 kW, IE3 from 7,5 kW.

IP 55 protection.

Motor suitable for operation with frequency converter.

Special features on request


- Special mechanical seal.
- Chrome-nickel steel AISI 316 pump-shaft.
- Higher or lower liquid or ambient temperatures.
- Other motor protection.
- Explosion proof construction in accordance with Directive 94/9 EEC (ATEX).
- Motor for other voltage.
- Frequency 60 Hz (as per 60 Hz data sheet).



End-Suction Centrifugal Pumps
standardized EN 733



Coverage chart $n \approx 2900$ rpm



Tolerances according to UNI EN ISO 9906:2012

Performance $n \approx 2900$ rpm

PUMP	PUMP	MOTOR	P2 kW	Q m³/h Q l/min	6,6	7,5	8,4	9,6	10,8	12	13,2	15	16,8	18,9	21	24	27	30	33	37,8	39	42	45	48
					110	125	140	160	180	200	220	250	280	315	350	400	450	500	550	630	650	700	750	800
B-N 32-125F/A	N 32-125F/A	71 M2	0,55	H m P3 kW	12,5 0,4	12,5 0,43	12 0,46	11,5 0,48	11 0,5	10,5 0,52	9,5 0,54	8 0,55	6 0,56											
B-N 32-125D/A	N 32-125D/A	80 M2 80 M2	0,75 1,1		18 0,63	18 0,67	17,5 0,7	17 0,75	16,5 0,79	16 0,83	15,5 0,86	14 0,9	12,5 0,93	11 0,95	8,5 0,97									
B-N 32-125A/A	N 32-125A/A	80 M2 90 S2	1,1 1,5		23 0,83	23 0,87	22,5 0,91	22 0,96	21,5 1,01	21 1,06	20,5 1,1	19,5 1,19	18 1,26	16 1,31	14 1,35	10 1,38								
B-N 32-125S/A	N 32-125S/A	90 S2	1,5		23,5 0,86	23,5 0,9	23 0,94	22,5 1	22 1,06	21,5 1,12	21 1,17	20,5 1,25	19 1,3	18,5 1,36	16,5 1,42	13 1,49								
B-N 32-160B/A	N 32-160B/A	90 S2 90 L2	1,5 2,2		29,5 1,1	29,5 1,17	29 1,23	28,5 1,30	27,5 1,37	27 1,43	26 1,48	25* 1,55	22,5* 1,63	20* 1,7	17,5* 1,75	12,5* 1,79								
B-N 32-160A/A	N 32-160A/A	90 L2 100 L2	2,2 3		35,5 1,56	35,5 1,64	35 1,71	34,5 1,81	34 1,9	33,5 1,98	33 2,05	32* 2,16	30* 2,24	28* 2,33	25* 2,4	21* 2,47	15* 2,5							
B-N 32-200D/A	N 32-200D/A	90 L2 100 L2	2,2 3		37,5 1,92	37 2	36 2,06	35 2,17	34 2,24	33 2,3	32 2,35	30 2,4	27 2,45	22 2,5										
B-N 32-200C/A	N 32-200C/A	100 L2	3		44,5 2,17	44 2,28	43,5 2,36	43 2,5	42 2,63	41 2,74	40 2,83	38,5 2,97	36 3,1	32 3,2										
B-N 32-200A/A	N 32-200A/A	112 M2 132 S2	4 5,5		57 2,9	56,5 3,1	56 3,18	55,5 3,35	54,5 3,51	53,5 3,67	52,5 3,8	51 4	49 4,2	46 4,4										
B-N 40-125F/A	N 40-125F/A	80 M2	1,1										14 0,96	13,5 1,00	13 1,04	12 1,07	11 1,10	9,5 1,13	8 1,13	6 1,13				
B-N 40-125C/A	N 40-125C/A	90 S2	1,5										17,5 1,21	17 1,26	16,5 1,32	16 1,38	15 1,44	13,5 1,49	12 1,53	10,5 1,56	7,5 1,57	6,5 1,57		
B-N 40-125A/A	N 40-125A/A	90 L2	2,2										22 1,50	22 1,57	21,5 1,65	21 1,72	20 1,82	19 1,91	18 1,98	16,5 2,04	14 2,10	13 2,11	11,5 2,13	
B-N 40-160C/A	N 40-160C/A	90 L2	2,2										23 1,55	22,5 1,63	22 1,72	21,5 1,80	20 1,90	18,5 1,99	16,5 2,06	14,5 2,12	11 2,17	10 2,17		
B-N 40-160B/A	N 40-160B/A	100 L2	3										29 2,08	28,8 2,18	28 2,30	27,5 2,41	26,5 2,55	25 2,67	23,5 2,78	21,5 2,87	18 2,97	17 2,99	14 3,02	
B-N 40-160A/A	N 40-160A/A	112 M2 132 S2	4 5,5										37 2,70	36,5 2,84	36,5 3,01	36 3,18	35 3,35	33,5 3,43	32 3,72	30,5 3,84	27 4,01	26 4,05	23,5 4,12	20 4,20
B-N 40-200D/A	N 40-200D/A	112 M2 132 S2	4 5,5										39 3,20	38 3,35	37 3,51	35,5 3,66	33,5 3,86	30,5 4,03	27 4,18	24 4,30	22,5 4,43			
B-N 40-200C/A	N 40-200C/A	112 M2 132 S2	4 5,5										41,5 3,44	40,5 3,59	39,5 3,78	38 3,95	36 4,15	33,5 4,32						
B-N 40-200B/A	N 40-200B/A	132 S2	5,5										50 3,96	49,5 4,18	48,5 4,41	47,5 4,64	45,5 4,92	43,5 5,17	41,5 5,39	37,5 5,60	30,5 5,87			
B-N 40-200A/A	N 40-200A/A	132 S2 132 S2	5,5 7,5										55 4,50	54,5 4,70	54 5,07	53 5,30	51 5,65	49 5,95						
B-N 40-200A/A	N 40-200A/A	132 S2	7,5										57,5 4,78	57 5,04	56,5 5,34	55,5 5,63	54,5 6,03	52,5 6,40	50,5 6,70	48 7,01	42,5 7,34	40,5 7,43	35 7,62	
B-N 40-250C/A	N 40-250C/A	160 M2	11										61 5,86	61 6,16	60,5 6,49	59,5 6,82	58,5 7,28	56,5 7,72	53,5 8,07	49,5 8,48	41,5 9,02	33,5 9,15	23,5 9,35	
B-N 40-250B/A	N 40-250B/A	160 M2	11										69,5 6,87	69,5 7,19	69 7,56	68,5 7,91	67 8,47	65,5 8,91	63,5 9,35	60,5 9,75	53,5 10,40	51 10,54	45 10,93	
B-N 40-250A/A	N 40-250A/A	160 M2	15										90 9,31	90 9,73	89,5 10,21	89 10,68	88,5 11,34	87 11,98	85 12,60	83 13,19	77,5 14,00	76 14,21	70,5 14,65	

N Standard construction. P₂ Rated motor power output. P₃ Pump power input. H Total head in m. * Maximum suction lift 1-2 m.
B-N Bronze construction.

N End-Suction Centrifugal Pumps standardized EN 733




Performance n ≈ 2900 rpm

PUMP B-N	PUMP N	MOTOR	P2 kW	Q m³/h	24	27	30	33	37,8	42	48	54	60	66	69	72	75	78	81	84	96	
					Q l/min	400	450	500	550	630	700	800	900	1000	1100	1150	1200	1250	1300	1350	1400	1600
B-N 50-125F/A	N 50-125F/A	90 L2	2,2	H m P3 kW			15,5 1,87	15 1,93	14 2,02	13,5 2,09	12 2,14	10 2,18	8 2,14	6 2,10								
B-N 50-125D/A	N 50-125D/A	100 L2	3				20 2,5	19,5 2,58	18,5 2,7	18 2,81	16,5 2,91	14,5 2,96	13 2,98	10,5 2,92	9 2,9	8 2,87						
B-N 50-125A/A	N 50-125A/A	112 M2	4				24 3,11	24 3,22	23 3,39	22,5 3,54	21 3,69	19,5 3,78	17,5 3,85	15 3,87	14 3,86	12,5 3,84	11,5 3,81	10 3,79				
B-N 50-125S/A	N 50-125S/A	112 M2 132 S2	4 5,5				26,5 3,38	26 3,52	25,5 3,71	24,5 3,87	23,5 4,04	22 4,18	20 4,25	18 4,29	16,5 4,28	15,5 4,26	14 4,26	13 4,24	11 4,22			
B-N 50-160B/A	N 50-160B/A	132 S2	5,5				31 4,30	30,5 4,48	29,5 4,71	28 4,90	26 5,11	24 5,28	21,5 5,35	19 5,40	17,5 5,40	15,5 5,36	13,5 5,32	11,5 5,30	9,5 5,22			
B-N 50-160A/A	N 50-160A/A	132 S2	7,5				38,5 5,44	38 5,67	37,5 6,02	36,5 6,31	34,5 6,67	32,5 6,95	30 7,18	27 7,30	25,5 7,34	24 7,38	22,5 7,41	20,5 7,42	19 7,46			
B-N 50-200B/A	N 50-200B/A	160 M2	11		48 5,81	47,5 6,13	47,5 6,44	47 6,73	45,5 7,18	44,5 7,55	42,5 8,02	40 8,43	37 8,77	33 9,01	30,5 9,08	28 9,15	25,5 9,19	23 9,23				
B-N 50-200A/A	N 50-200A/A	160 M2	11		55 6,92	55 7,29	54,5 7,65	54,5 7,99	53,5 8,56	52 8,99	50 9,57	48 10,05	45 10,45	41,5 10,75	39,5 10,89	37 10,98	35 11,11	32,5 11,15				
B-N 50-200S/A	N 50-200S/A	160 M2	15		60 7,56	60 7,98	59,5 8,39	59,5 8,79	58,5 9,38	57,5 9,82	55,5 10,48	53,5 11,05	50,5 11,54	47 11,85	45 12,02	43 12,20	40,5 12,30	37 12,40				
B-N 50-250C/A	N 50-250C/A	160 M2	11		55 7,28	54,5 7,68	54 8,06	53 8,42	51,5 8,98	49,5 9,42	46,0 9,99	41,5 10,42	35,5 10,75	28,5 10,95	24,5 11,08							
B-N 50-250B/A	N 50-250B/A	160 M2	15		69 9,62	68,5 10,08	68 10,58	67,5 11,05	66 11,68	64 12,32	61 13,05	57 13,77	52,5 14,20	46,5 14,77	43 14,98							
B-N 50-250A/A	N 50-250A/A	160 L2	18,5		80,5 11,75	80,5 12,33	80 12,92	79,5 13,56	78,5 14,47	77 15,20	74,5 16,10	71,5 16,94	67 17,65	61,5 18,25	58,5 18,55							
B-N 50-250S/A	N 50-250S/A	180 M2	22		88,5 12,76	88,5 13,46	88 14,15	87 14,85	86 15,93	84 16,84	81,5 17,92	78,5 19,02	75 19,91	71 20,62	68,5 20,96							

4

PUMP B-N	PUMP N	MOTOR	P2 kW	Q m³/h	24	27	30	33	37,8	42	48	54	60	66	72	84	96	108	120	132	150	
					Q l/min	400	450	500	550	630	700	800	900	1000	1100	1200	1400	1600	1800	2000	2200	2500
B-N 65-125E/B	N 65-125E/B	112 M2	4	H m P3 kW					16,5 2,86	16,4 2,99	16,2 3,17	15,9 3,34	15,5 3,5	15,1 3,64	14,3 3,81	13,2 3,94	11,4 4,03	9,2 4				
B-N 65-125C/B	N 65-125C/B	132 S2	5,5						21,1 3,68	21 3,86	20,8 4,11	20,6 4,35	20,3 4,57	19,9 4,77	19,1 5,02	18,2 5,25	16,5 5,41	14,4 5,5	11,8 5,49			
B-N 65-125A/B	N 65-125A/B	132 S2	7,5						25,9 4,71	25,8 4,92	25,6 5,21	25,4 5,5	25,1 5,77	24,8 6,03	24,1 6,38	23,3 6,69	21,9 7,02	20 7,25	17,6 7,36			
B-N 65-160D/B	N 65-160D/B	132 S2	7,5								24,3 5,11	24,1 5,44	23,9 5,75	23,6 6,05	23,1 6,45	22,3 6,8	20,8 7,15	18,8 7,4	16,3 7,52			
B-N 65-160C/B	N 65-160C/B	160 M2	11								28,1 5,89	28 6,26	27,8 6,61	27,6 6,96	27,1 7,44	26,3 7,87	24,9 8,37	23,1 8,74	20,7 8,98	17,7 9,06		
B-N 65-160B/B	N 65-160B/B	160 M2	11								32,6 7,04	32,5 7,44	32,3 7,84	32 8,22	31,5 8,76	30,8 9,25	29,5 9,84	27,9 10,33	25,7 10,7	23,0 10,96		
B-N 65-160AR	N 65-160AR	160 M2	15								36,4 7,98	36,3 8,45	36,2 8,91	35,9 9,36	35,5 9,99	34,8 10,57	33,7 11,27	32,1 11,85	30,0 12,33	27,5 12,71		
B-N 65-160A/B	N 65-160A/B	160 M2	15								40,5 8,91	40,4 9,44	40,2 9,96	40 10,47	39,5 11,19	38,8 11,85	37,6 12,64	36,1 13,33	34,2 13,92	31,7 14,42		
B-N 65-200C/A	N 65-200C/A	160 M2	15								44 10,4	43,5 11	43 11,6	42,5 12,1	42 12,8	41 13,2	39,5 13,8	37,5 14,6	35 15,2	31 16,1	27* 17,2	
B-N 65-200B/A	N 65-200B/A	160 L2	18,5								50 12,25	49,5 12,85	49 13,45	48,5 14	47,5 14,75	46,5 15,4	44,5 16,3	42 17,1	39 17,7	35* 18,4		
B-N 65-200A/A	N 65-200A/A	180 M2	22								56,5 13,6	56 14,3	55,5 15	55 15,7	54,5 16,65	53,5 17,6	51 18,6	48,5 19,5	45,5 20,4	41,5* 21		
B-N 65-250C/A	N 65-250C/A	180 M2	22								64 15,3	63,5 16,2	63 17,1	61,5 18	60 19	57,5 20	54,5* 21	50* 22				
B-N 65-250B/A	N 65-250B/A	200 L2	30								79,5 20,2	79 21,3	78,5 22,3	78 23,3	77 24,7	75 26	72* 27,7	67* 29,3				
B-N 65-250A/A	N 65-250A/A	200 L2	37								90 23,6	89,5 25	89 26,2	88,5 27,3	87,5 29	86 30,5	83,5* 32,5	78,5* 34				

PUMP B-N	PUMP N	MOTOR	P2 kW	Q m³/h	60	66	75	84	96	108	120	132	150	168	180	192	210	240	270	300	
					Q l/min	1000	1100	1250	1400	1600	1800	2000	2200	2500	2800	3000	3200	3500	4000	4500	5000
B-N 80-160E/B	N 80-160E/B	132 S2 160 M2	7,5 11	H m P3 kW			21,5 6,81	20,9 6,92	19,9 7,05	18,7 7,15	17,4 7,22	15,9 7,26	13,4 7,27	10,6 7,21							
B-N 80-160D/B	N 80-160D/B	160 M2	11				25,2 8	24,5 8,22	23,5 8,49	22,4 8,73	21,1 8,93	19,6 9,09	17,2 9,23	14,4 9,23							
B-N 80-160C/B	N 80-160C/B	160 M2	11				28,7 9,04	28,2 9,35	27,4 9,74	26,4 10,09	25,1 10,39	23,8 10,65	21,3 10,91	18,5 10,99	16,4 10,93						
B-N 80-160B/B	N 80-160B/B	160 M2	15				34,8 11,37	34,5 11,83	33,8 12,42	33 13	32,1 13,53	30,9 14,01	28,9 14,63	26,4 15,07	24,5 15,26	22,4 15,34					
B-N 80-160A/B	N 80-160A/B	160 L2	18,5				39,9 13,25	39,6 13,82	39 14,58	38,2 15,3	37,4 15,99	36,4 16,62	34,5 17,45	32,2 18,09	30,3 18,4	28,1 18,59					
B-N 80-200B/A	N 80-200B/A	180 M2	22				46,5 15,7	46 16,6	45,5 17,7	44,5 18,6	43,5 19,4	42 20,2	39* 21,3	35,5* 21,8	32* 22						
B-N 80-200A/A	N 80-200A/A	200 L2	30				56 20	55,5 21,1	55 22,3	54 23,5	53 24,7	52 25,7	49,5* 27,2	46* 28,5	43* 29,3						
B-N 80-250E/A	N 80-250E/A	180 M2	22				51 16,2	50 17,1	48,5 18,2	46,5 19,1	44,5 20	42 20,6	38* 21,4	33* 21,9	29* 22						
B-N 80-250D/A	N 80-250D/A	200 L2	30				65 21,3	64 22,3	62,5 24	61 25,3	59 26,5	56,5 27,5	53* 28,6	49* 29,4	45,5* 29,8	41* 30					
B-N 80-250C/A	N 80-250C/A	200 L2	37				73,5 24,6	73 26	72 27,8	70,5 29,5	69 31	67 32,4	63* 33,8	59* 35,2	55,5* 35,7	51,5* 36,2					
B-N 80-250B/A	N 80-250B/A	225 M2	45				84 29	83,5 30,7	82,5 32,9	81,5 35	80 36,7	78 38,3	74,5* 40,1	70,5* 41,8	67* 43	63* 44,1					
B-N 80-250A/A	N 80-250A/A	250 M2	55				95 33,7	94,5 35,6	93,5 38,1	92,5 40,5	91,5 42,7	90 44,8	87,5* 47,4	84* 50	80,5* 51,5	76,5* 53					
B-N 100-200E/A	N 100-200E/A	160 L2	18,5							30 14,5	29,5 15,1	29 15,7	28 16,6	27 17,2	26 17,6	25 17,9	23 18,3	19* 18,4			
B-N 100-200D/A	N 100-200D/A	180 M2	22							36 17,1	35,5 17,8	35 18,5	34 19,5	33 20,2	32 20,7	31 21,1	29 21,6	24,5* 22	19* 22		
B-N 100-200C/A	N 100-200C/A	200 L2	30							45 22	44,5 22,9	44 23,8	43,5 25,1	42,5 26,2	41,5 26,9	40,5 27,5	39 28,3	34,5* 29,4	29* 29,8	22* 30	
B-N 100-200B/A	N 100-200B/A	200 L2	37							54 27,1	53,5 28,3	53 29,4	52,5 30,9	51,5 32,2	50,5 33,3	49,5 34	48 34,9	44* 36,3	38,5* 37	32* 37,2	
B-N 100-200A/A	N 100-200A/A	225 M2	45							61,5 31	61 32,4	60,5 33,8	60 35,8	59,5 37,7	58,5 39	58 40	56,5 41,5	53* 43,5	48* 45	42* 45,5	
B-N 100-250B/A	N 100-250B/A	250 M2	55							73,5 39	73 40,6	72,5 42,1	71,5 44,3	70 46,4	68,5 47,8	67 48,8	65 50,5	61* 52,9	55,5* 54,7	48,5* 55,8	
B-N 100-250A/A	N 100-250A/A	280 S2	75						91 50	90,5 52,5	90 55	89,5 58,3	88,5 61,5	88 63,5	87 65,5	85 68	81* 71,5	75* 74,5	67* 75		

Coverage chart $n \approx 1450$ rpm

Tolerances according to UNI EN ISO 9906:2012

Performance $n \approx 1450$ rpm

PUMP	PUMP	MOTOR	P ₂ kW	Q m³/h	2,4	3	3,6	4,2	4,8	5,4	6	6,6	7,5	8,4	9,6	10,8	12	13,2		
				Q l/min	40	50	60	70	80	90	100	110	125	140	160	180	200	220		
B-N4 32-125F/A	N4 32-125F/A	71 M4	0,25	H m P ₃ kW	3 0,04	2,9 0,047	2,8 0,051	2,7 0,055	2,6 0,059	2,5 0,063	2,4 0,067	2,2 0,07	1,8 0,075	1,5 0,08						
B-N4 32-125D/A	N4 32-125D/A	71 M4	0,25		4,6 0,07	4,5 0,075	4,4 0,08	4,3 0,085	4,2 0,09	4,1 0,095	4 0,1	3,8 0,105	3,5 0,115	3,2 0,12	2,6 0,13	2 0,13				
B-N4 32-125A/A	N4 32-125A/A	71 M4	0,25		5,7 0,09	5,6 0,1	5,5 0,11	5,4 0,115	5,3 0,12	5,2 0,125	5,1 0,13	5 0,135	4,8 0,145	4,5 0,15	4 0,16	3,3 0,17				
B-N4 32-160B/A	N4 32-160B/A	71 M4	0,37		7,6 0,13	7,5 0,14	7,4 0,15	7,3 0,16	7,2 0,17	7,1 0,18	6,9 0,19	6,7 0,2	6,3 0,21	5,9 0,215	5,2 0,23	4,2 0,235				
B-N4 32-160A/A	N4 32-160A/A	71 M4	0,37		9 0,17	8,95 0,18	8,9 0,19	8,8 0,2	8,7 0,21	8,6 0,22	8,5 0,23	8,3 0,24	7,9 0,26	7,5 0,275	6,8 0,29	6 0,305	5,1 0,315			
B-N4 32-200B/A	N4 32-200B/A	80 M4	0,55		12,5 0,28	12,4 0,3	12,3 0,315	12,2 0,33	12 0,345	11,8 0,36	11,6 0,375	11,2 0,39	10,6 0,41	10 0,43	8,9 0,455	7,6 0,48	6,2 0,5	4,7 0,515		
B-N4 32-200A/A	N4 32-200A/A	80 M4	0,75		14,3 0,35	14,2 0,375	14,1 0,4	14 0,42	13,9 0,44	13,7 0,46	13,5 0,48	13,3 0,5	12,9 0,525	12,3 0,55	11,3 0,585	10,2 0,61	8,9 0,635	7,5 0,655		

PUMP	PUMP	MOTOR	P ₂ kW	Q m³/h	5,4	6	6,6	7,5	8,4	9,6	10,8	12	13,2	15	16,8	18,9	21	24	27	30
				Q l/min	90	100	110	125	140	160	180	200	220	250	280	315	350	400	450	500
B-N4 40-160C/A	N4 40-160C/A	71 M4	0,37	H m P ₃ kW	6,1 0,17	6 0,18	5,9 0,19	5,9 0,2	5,8 0,21	5,6 0,23	5,4 0,24	5,2 0,25	5 0,26	4,5 0,27	3,9 0,28	3,1 0,29	2,3 0,3			
B-N4 40-160B/A	N4 40-160B/A	80 M4	0,55		7,6 0,22	7,6 0,23	7,6 0,24	7,6 0,26	7,6 0,27	7,3 0,29	7,1 0,31	6,9 0,32	6,6 0,34	6,3 0,36	5,7 0,38	5 0,39	4 0,4	2,7 0,41		
B-N4 40-160A/A	N4 40-160A/A	80 M4	0,75		9,6 0,28	9,6 0,3	9,6 0,31	9,6 0,33	9,4 0,35	9,3 0,37	9,1 0,4	9 0,42	8,8 0,44	8,4 0,47	7,9 0,49	7,2 0,51	6,4 0,53	5,1 0,55	3,5 0,56	
B-N4 40-200B/A	N4 40-200B/A	90 S4	1,1		13 0,51	12,9 0,53	12,8 0,53	12,7 0,54	12,6 0,57	12,4 0,6	12,2 0,63	12 0,66	11,5 0,68	10,8 0,71	10 0,75	8,6 0,78	7 0,81	5,3 0,83		
B-N4 40-200A/A	N4 40-200A/A	90 S4	1,1		14,8 0,59	14,7 0,6	14,6 0,6	14,5 0,61	14,4 0,64	14,2 0,67	14,2 0,71	14 0,74	13,8 0,77	13,6 0,8	13 0,85	12,2 0,9	11,3 0,94	10 0,97		
B-N4 40-250C/A	N4 40-250C/A	90 L4	1,5		17,4 0,689	17,3 0,715	17,2 0,74	17,2 0,779	17 0,817	16,8 0,865	16,6 0,912	16,3 0,967	16 1,018	15,1 1,092	13,8 1,134	12,1 1,178	10,4 1,248	7,2 1,301	2,8 1,348	
B-N4 40-250B/A	N4 40-250B/A	100 LA4	2,2		21,4 0,908	21,5 0,942	21,4 0,99	21,3 1,025	21,2 1,075	21 1,140	20,9 1,203	20,8 1,266	20,5 1,327	20 1,405	19,5 1,482	18,3 1,567	16,4 1,645	13,3 1,752	10 1,815	5 1,887
B-N4 40-250A/A	N4 40-250A/A	100 LB4	3		22,9 1,068	22,8 1,104	22,9 1,15	22,9 1,193	22,8 1,246	22,5 1,316	22,5 1,385	22,2 1,454	22 1,521	21,8 1,638	21,4 1,733	20,4 1,817	18,9 1,933	16 2,068	12,6 2,168	8 2,267

N4 Standard construction.

P₂ Rated motor power output.

H Total head in m.

* Maximum suction lift 1-2 m.

B-N4 Bronze construction.

P₃ Pump power input.



End-Suction Centrifugal Pumps standardized EN 733



Performance n ≈ 1450 rpm

PUMP B-N4	PUMP N4	MOTOR	P ₂ kW	Q m ³ /h Q l/min	10,8	12	13,2	15	16,8	18,9	21	24	27	30	33	37,8	42	48		
					180	200	220	250	280	315	350	400	450	500	550	630	700	800		
B-N4 50-125F/A	N4 50-125F/A	71 M4	0,37	H m P ₃ kW	4,2 0,209	4,1 0,219	4,1 0,229	4,0 0,243	3,9 0,256	3,7 0,268	3,5 0,279	3,2 0,291	2,8 0,292	2,3 0,291	1,8 0,287					
B-N4 50-125D/A	N4 50-125D/A	80 M4	0,55		5,2 0,27	5,2 0,29	5,2 0,3	5,1 0,32	5,0 0,33	4,8 0,35	4,6 0,37	4,3 0,38	3,9 0,39	3,4 0,39	2,8 0,39					
B-N4 50-125A/A	N4 50-125A/A	80 M4	0,75		6,2 0,332	6,1 0,348	6,1 0,363	6,0 0,385	5,9 0,405	5,8 0,426	5,6 0,446	5,3 0,469	5,0 0,486	4,5 0,495	3,9 0,498	2,9 0,493				
B-N4 50-125S/A	N4 50-125S/A	80 M4	0,75		6,8 0,366	6,7 0,382	6,7 0,399	6,6 0,422	6,5 0,444	6,4 0,471	6,2 0,495	6,0 0,524	5,6 0,545	5,2 0,558	4,6 0,564	3,6 0,561				
B-N4 50-160B/A	N4 50-160B/A	90 S4	1,1		8,2 0,449	8,2 0,469	8,2 0,496	8,1 0,524	8 0,555	7,8 0,584	7,6 0,610	7,2 0,643	6,7 0,671	6,2 0,683	5,5 0,692	4,4 0,687	3,3 0,673			
B-N4 50-160A/A	N4 50-160A/A	90 S4	1,1		9,6 0,555	9,6 0,578	9,6 0,600	9,5 0,632	9,5 0,670	9,3 0,705	9,1 0,742	8,8 0,778	8,3 0,811	7,8 0,833	7,2 0,850	6,1 0,862	4,9 0,861	3,1 0,844		
B-N4 50-200C/A	N4 50-200C/A	90 S4	1,1		11,8 0,617	11,8 0,647	11,7 0,682	11,7 0,720	11,5 0,759	11,3 0,801	10,9 0,841	10,4 0,888	9,8 0,927	9 0,957	8,1 0,979	6,3 1,005	4,7 1,010			
B-N4 50-200B/A	N4 50-200B/A	90 L4	1,5		13,4 0,772	13,4 0,807	13,4 0,840	13,3 0,889	13,1 0,949	12,9 0,998	12,6 1,051	12,1 1,115	11,5 1,171	10,8 1,213	9,9 1,251	8,2 1,278	6,4 1,299	3,7 1,301		
B-N4 50-200A/A	N4 50-200A/A	100 L4	2,2		14,9 0,883	14,9 0,923	14,9 0,962	14,9 1,019	14,8 1,074	14,6 1,135	14,4 1,194	14 1,273	13,4 1,345	12,8 1,409	12 1,464	10,4 1,535	8,6 1,576	6 1,596		
B-N4 50-250D/A	N4 50-250D/A	100 L4	2,2		14,5 0,843	14,4 0,866	14,3 0,929	14 0,990	13,7 1,049	13,4 1,098	13 1,160	12,2 1,230	11,2 1,300	9,7 1,364	8,1 1,395	5,4 1,435	2,3 1,468			
B-N4 50-250C/A	N4 50-250C/A	100 L4	2,2		17,8 1,091	17,8 1,140	17,7 1,188	17,5 1,258	17,2 1,324	16,8 1,397	16,4 1,465	15,7 1,554	14,9 1,633	13,8 1,700	12,4 1,755	9,7 1,818	6,8 1,844			
B-N4 50-250B/A	N4 50-250B/A	100 L4	3		20,7 1,374	20,7 1,437	20,7 1,499	20,6 1,591	20,4 1,680	20 1,781	19,5 1,878	18,9 2,009	18,2 2,130	17,1 2,241	15,9 2,320	13,2 2,448	10,6 2,510	5,8 2,580		
B-N4 50-250A/A	N4 50-250A/A	112 M4	4		22,7 1,493	22,7 1,561	22,6 1,628	22,5 1,728	22,4 1,825	22,1 1,935	21,6 2,042	21 2,186	20,2 2,322	19,4 2,445	18,3 2,557	16,4 2,706	13,6 2,804	9 2,893		

4

PUMP B-N4	PUMP N4	MOTOR	P ₂ kW	Q m ³ /h Q l/min	21	24	27	30	33	37,8	42	48	54	60	66	75	84	96	108	120
					350	400	450	500	550	630	700	800	900	1000	1100	1250	1400	1600	1800	2000
B-N4 65-125E/B	N4 65-125E/B	80 M4	0,75	H m P ₃ kW	4,1 0,38	4,05 0,4	3,98 0,41	3,88 0,44	3,78 0,45	3,58 0,48	3,3 0,49	2,85 0,5	2,3 0,5							
B-N4 65-125C/B	N4 65-125C/B	80 M4	0,75		5,25 0,49	5,2 0,51	5,15 0,54	5,08 0,58	4,98 0,6	4,78 0,63	4,55 0,65	4,13 0,69	3,6 0,69	2,95 0,69						
B-N4 65-125A/B	N4 65-125A/B	90 S4	1,1		6,45 0,61	6,4 0,65	6,35 0,69	6,28 0,73	6,2 0,75	6,03 0,8	5,83 0,84	5,48 0,91	5 0,91	4,4 0,93						
B-N4 65-160C/B	N4 65-160C/B	90 S4	1,1		6 0,56	6 0,6	5,9 0,63	5,9 0,63	5,9 0,71	5,7 0,77	5,5 0,81	5,2 0,86	4,7 0,9	4 0,91						
B-N4 65-160B/B	N4 65-160B/B	90 S4	1,1		7,2 0,68	7,1 0,73	7,1 0,77	7 0,77	7 0,86	6,8 0,92	6,6 0,97	6,3 1,03	5,8 1,07	5,2 1,11	4,5 1,12					
B-N4 65-160A/B	N4 65-160A/B	90 L4	1,5		8,8 0,87	8,8 0,93	8,7 0,98	8,7 0,98	8,6 1,09	8,5 1,17	8,3 1,24	8 1,32	7,6 1,39	7,1 1,44	6,4 1,48	5,2 1,51				
B-N4 65-160S	N4 65-160S	100 L4	2,2		10,2 1,09	10,2 1,15	10,1 1,22	10,1 1,22	10 1,34	9,9 1,44	9,7 1,52	9,4 1,62	9,1 1,71	8,6 1,79	8 1,86	7 1,93	5,7 1,96			
B-N4 65-200B/A	N4 65-200B/A	100 L4	2,2		11,9 1,25	11,8 1,33	11,7 1,4	11,6 1,47	11,4 1,53	11,1 1,62	10,8 1,69	10,2 1,78	9,5 1,86	8,7 1,93	7,8 1,98	6,2 2	4,3 2			
B-N4 65-200A/A	N4 65-200A/A	100 L4	3		14,1 1,57	14 1,66	13,9 1,75	13,8 1,84	13,7 1,91	13,4 2,02	13,1 2,13	12,6 2,24	11,9 2,35	11,1 2,46	10,2 2,56	8,8 2,65	7,2 2,7			
B-N4 65-250B/A	N4 65-250B/A	112 M4	4		18 2,02	17,9 2,14	17,8 2,26	17,7 2,38	17,6 2,5	17,3 2,66	16,9 2,8	16,3 3	15,4 3,18	14,4 3,36	13,1 3,5	10,8 3,68	8,5 3,82			
B-N4 65-250A/A	N4 65-250A/A	132 S4	5,5		21,9 2,74	21,8 2,88	21,7 3,02	21,6 3,16	21,5 3,3	21,2 3,52	20,8 3,72	20,2 3,97	19,5 4,22	18,5 4,43	17,5 4,63	15,4 4,91	12,8 5,15			
B-N4 65-315C/A	N4 65-315C/A	132 S4	5,5		25,8 3,12	25,7 3,31	25,5 3,49	25,3 3,67	25 3,83	24,4 4,05	23,8 4,25	22,8 4,5	21,5 4,75	20 4,96	18,2 5,12	15 5,3	11 5,44			
B-N4 65-315B/A	N4 65-315B/A	132 M4	7,5		31 3,97	31 4,23	30,9 4,45	30,8 4,65	30,6 4,85	29,7 5,15	28,8 5,4	27,8 5,75	26,5 6,1	25,2 6,4	22,2 6,65	18,6 7	16,6 7,2			
B-N4 65-315A/A	N4 65-315A/A	160 M4	11		35,9 4,8	35,9 5,1	35,8 5,4	35,7 5,6	35,5 5,8	35,1 6,15	34,6 6,5	33,8 6,9	32,8 7,3	31,6 7,6	30,2 7,9	27,8 8,3	25 8,7			

PUMP B-N4	PUMP N4	MOTOR	P2 kW		Q m³/h	30	33	37,8	42	48	54	60	66	75	84	96	108	120	132	150	168
					Q l/min	500	550	630	700	800	900	1000	1100	1250	1400	1600	1800	2000	2200	2500	2800
B-N4 80-160C/B	N4 80-160C/B	90 S4	1,1	H m Ps kW	6,1 0,87	6,1 0,88	5,9 0,9	5,8 0,92	5,5 0,95	5,2 0,98	4,9 1	4,6 1,02	4 1,03	3,3 1,04							
B-N4 80-160B/B	N4 80-160B/B	90 L4	1,5		7,8 1,14	7,7 1,16	7,6 1,2	7,5 1,23	7,3 1,27	7 1,31	6,8 1,34	6,4 1,37	5,9 1,41	5,2 1,44	4,1 1,46						
B-N4 80-160A/B	N4 80-160A/B	100 L4	2,2		10 1,49	10 1,53	9,9 1,6	9,8 1,66	9,7 1,74	9,5 1,82	9,3 1,9	8,5 1,97	8 2,07	7 2,15	5,9 2,22	5,9 2,24					
B-N4 80-200C/A	N4 80-200C/A	100 L4	2,2		10,3 1,56	10,2 1,62	10,1 1,7	10 1,77	9,8 1,86	9,5 1,93	9,1 2	8,6 2,06	7,7 2,13	6,6 2,18	4,6 2,2						
B-N4 80-200B/A	N4 80-200B/A	100 L4	3		12,1 1,8	12 1,88	11,9 2	11,8 2,1	11,7 2,22	11,4 2,33	11,1 2,43	10,6 2,52	9,8 2,62	9 2,68	7,5 2,72	5,7 2,72					
B-N4 80-200A/A	N4 80-200A/A	112 M4	4		13,9 2,13	13,8 2,22	13,7 2,35	13,6 2,48	13,5 2,65	13,3 2,8	13 2,94	12,6 3,05	11,8 3,2	11 3,35	9,6 3,44	7,9 3,46	6 3,44				
B-N4 80-250C/A	N4 80-250C/A	112 M4	4		16,9 2,37	16,8 2,5	16,7 2,65	16,6 2,8	16,3 3	15,9 3,2	15,4 3,35	14,8 3,49	13,9 3,68	12,7 3,83	11,1 3,97	9,3 3,98	7,2 3,88				
B-N4 80-250B/A	N4 80-250B/A	132 S4	5,5		20,7 3,25	20,6 3,38	20,5 3,58	20,4 3,75	20,3 4	20 4,23	19,6 4,42	19,1 4,6	18,2 4,87	17,1 5,13	15,4 5,35	13,5 5,49	11,4 5,55	9* 5,45			
B-N4 80-250A/A	N4 80-250A/A	132 M4	7,5		23,7 3,94	23,7 4,1	23,6 4,33	23,5 4,54	23,3 4,83	23 5,08	22,7 5,33	22,2 5,58	21,5 5,91	20,5 6,23	19 6,54	17,2 6,82	15,1 6,98	12,7* 7,05			
B-N4 80-315C/A	N4 80-315C/A	160 M4	11		28,8 4,63	28,8 4,85	28,7 5,15	28,6 5,45	28,3 5,88	27,9 6,23	27,4 6,58	26,8 6,92	25,8 7,4	24,6 7,85	22,6 8,35	20,4 8,75	17,8 9,05	15* 9,2			
B-N4 80-315B/A	N4 80-315B/A	160 M4	11		32,3 5,7	32,3 5,9	32,2 6,23	32,1 6,55	31,9 7	31,6 7,45	31,2 7,85	30,7 8,2	29,8 8,7	28,8 9,2	27 9,8	25,1 10,3	22,9 10,8	20* 11			
B-N4 80-315A/A	N4 80-315A/A	160 L4	15		37,4 6,47	37,4 6,77	37,3 7,3	37,2 7,65	37,1 8,25	37 8,85	36,7 9,35	36,3 9,8	35,6 10,55	34,7 11,25	33,2 12,1	31,3 12,8	29 13,5	26,4* 14			
B-N4 80-400C/A	N4 80-400C/A	180 M4	18,5		46,5 9,75	46,3 10,25	46,1 10,85	45,8 11,25	45,2 11,9	44,5 12,55	43,5 13,2	42,4 13,85	40 14,8	37,2 15,5	32,5 16,5	26,2 17,5	18,5 18,5				
B-N4 80-400B/A	N4 80-400B/A	180 L4	22		54 11,5	53,8 11,9	53,6 12,5	53,3 13,1	53 13,95	52,4 14,7	51,6 15,45	50,6 16,15	48,7 17,35	46,1 18,4	42 19,5	36,5 20,6	29,5 21,55	21* 22,3			
B-N4 80-400A/A	N4 80-400A/A	200 L4	30		61,5 12,65	61,4 13,2	61,3 14	61,1 14,7	60,8 15,6	60,2 16,5	59,4 17,4	58,4 18,25	56,5 19,4	54 20,55	50,5 22,1	45,5 23,5	40 24,9	32,5* 26			



End-Suction Centrifugal Pumps standardized EN 733



Performance n ≈ 1450 rpm

PUMP B-N4	PUMP N4	MOTOR	P ₂ kW	Q m³/h	48	54	60	66	75	84	96	108	120	132	150	168	180	192	210	
				Q l/min	800	900	1000	1100	1250	1400	1600	1800	2000	2200	2500	2800	3000	3200	3500	
B-N4 100-200C/A	N4 100-200C/A	100 L4	3	H m P ₃ kW	9,4 2,1	9,3 2,2	9,2 2,3	9,1 2,4	8,9 2,5	8,5 2,6	8 2,7	7,3 2,8	6,5 2,85	5,6 2,9	4 2,85					
B-N4 100-200B/A	N4 100-200B/A	112 M4	4		12 2,65	11,9 2,8	11,8 2,95	11,7 3,1	11,5 3,3	11,2 3,45	10,7 3,65	10 3,85	9,3 3,95	8,4 4	6,7 3,95	4,5 3,8				
B-N4 100-200A/A	N4 100-200A/A	132 S4	5,5		15,2 3,65	15,2 3,85	15,1 4	15 4,15	14,9 4,4	14,7 4,6	14,3 4,85	13,8 5,1	13,1 5,3	12,2 5,45	10,7 5,55	9 5,65	7,5* 5,85	6* 5,55		
B-N4 100-250B/A	N4 100-250B/A	132 M4	7,5		19,5 4,8	19,5 5	19,4 5,2	19,3 5,4	19 5,75	18,7 6,05	18,2 6,4	17,5 6,7	16,6 7	15,6 7,3	13,8 7,5	11,7 7,5	10 7,45	8,4 7,35	5,5 7,15	
B-N4 100-250A/A	N4 100-250A/A	160 M4	11		22,3 5,5	22,3 5,8	22,2 6,05	22,1 6,25	21,9 6,6	21,7 6,95	21,2 7,35	20,5 7,75	19,8 8,1	18,8 8,35	17,1 8,7	15 9	13,4 9,05	11,7 9,5	8,9 8,9	
B-N4 100-315C/A	N4 100-315C/A	160 M4	11		26,9 6,6	26,9 7	26,8 7,35	26,6 7,65	26,2 8,1	25,7 8,5	24,9 9	23,8 9,5	22,7 9,85	21,3 10,2	18,9 10,7	15,9 10,9	13,7 11	11,3* 11		
B-N4 100-315B/A	N4 100-315B/A	160 L4	15		31,5 7,8	31,5 8,25	31,4 8,65	31,3 9	31,2 9,6	30,8 10,2	30,2 10,9	29,3 11,5	28,2 12,1	26,9 12,6	24,6 13,3	21,8 13,9	19,8 14,1	17,6* 14,4	14* 14,4	
B-N4 100-315A/A	N4 100-315A/A	180 M4	18,5		36,9 9,7	36,9 10,2	36,8 10,7	36,7 11,2	36,6 11,9	36,4 12,5	36 13,3	35,3 14,1	34,5 14,9	33,4 15,6	31,4 16,6	29,2 17,4	27,2 17,9	25,3* 18,3	22,2* 18,75	
B-N4 100-400C/A	N4 100-400C/A	180 L4	22		41,3 11,1	41,2 11,8	41,1 12,5	41 13,2	40,7 14	40,4 14,8	39,8 16	39 17	38 18	36,5 18,9	34 20	31 21	28,7 21,7	26 22		
B-N4 100-400B/A	N4 100-400B/A	200 L4	30		50,2 15,2	50,1 16	50 16,8	49,9 17,4	49,7 18,4	49,4 19,3	48,8 20,6	48 21,8	47,1 23	46 24,2	44 25,7	41,3 27	39,5 27,8	37 28,5	33,5* 29,4	
B-N4 100-400A/A	N4 100-400A/A	225 S4	37		58,2 17,8	58,1 18,75	58 19,7	57,9 20,5	57,8 21,7	57,6 22,9	57,2 24,4	56,3 25,9	55,7 27,4	54,5 28,8	52,7 30,9	50,5 32,7	49 33,85	47 35	44* 36,5	

PUMP B-N4	PUMP N4	MOTOR	P ₂ kW	Q m³/h	84	96	108	120	132	150	168	180	192	210	240	270	300	330		
				Q l/min	1400	1600	1800	2000	2200	2500	2800	3000	3200	3500	4000	4500	5000	5500		
B-N4 125-250E/A	N4 125-250E/A	132 S4	5,5	H m P ₃ kW	11 4,2	10,8 4,5	10,5 4,75	10,1 4,95	9,7 5,05	9,1 5,2	8,3 5,35	7,8 5,45	7,2 5,5	6,2 5,5	4,4 5,35					
B-N4 125-250D/A	N4 125-250D/A	132 M4	7,5		14 5,4	13,9 5,7	13,7 5,95	13,4 6,2	13 6,45	12,4 6,75	11,6 7	11 7,1	10,4 7,2	9,4 7,35	7,4 7,4	5,1 7,1				
B-N4 125-250C/A	N4 125-250C/A	160 M4	11		16,7 6,3	16,6 6,7	16,4 7,1	16,2 7,4	15,9 7,65	15,4 8,05	14,6 8,4	14,1 8,6	13,5 8,75	12,5 9	10,4 9,2	8,2 9,2	5,8 9,05			
B-N4 125-250B/A	N4 125-250B/A	160 M4	11		19,3 7,8	19,2 8,25	19,1 8,7	18,9 9,1	18,7 9,45	18,2 10	17,5 10,35	17 10,6	16,3 10,85	15,3 11,1	13,3 11,4	10,9 11,45	8,2 11,3			
B-N4 125-250A/A	N4 125-250A/A	160 L4	15		22,7 9,2	22,7 9,75	22,6 10,3	22,4 10,85	22,2 11,3	21,8 12	21,2 12,6	20,8 12,95	20,1 13,25	19,33 13,75	17,4 14,3	15 14,5	12,4 14,55	9,3 14,4		
B-N4 125-315C/A	N4 125-315C/A	180 M4	18,5		27,9 11,5	27,8 12,15	27,7 12,8	27,6 13,4	27,4 14	26,5 14,7	25,6 15,4	24,9 15,8	24 16,2	22,8 16,7	20,2 17,3	17 17,7	13,5 18	9,5* 18		
B-N4 125-315B/A	N4 125-315B/A	180 L4	22		31,8 12,75	31,7 13,6	31,6 14,45	31,5 15,3	31,1 15,9	30,6 16,8	29,7 17,7	29,1 18,4	28,5 19	27,3 19,7	24,9 20,6	22 21,4	18,5 22	14,3* 22,1		
B-N4 125-315A/A	N4 125-315A/A	200 L4	30		36,8 15,5	36,8 16,5	36,7 17,5	36,6 18,3	36,4 19,1	35,9 20,4	35,2 21,6	34,7 22,4	34,2 23,1	33,2 24,15	31 25,6	28,4 26,6	25,3 27,6	21,6* 28,45		
B-N4 125-400C/A	N4 125-400C/A	225 S4	37		45,4 19,4	45,3 20,7	45,2 22	45,1 23,3	44,9 24,6	44,4 26,5	43,7 28,2	43 29,3	42 30,2	40 31,4	37 33,4	33 35	28,5* 35,9	23,5* 36,75		
B-N4 125-400B/A	N4 125-400B/A	225 M4	45		51,4 22,9	51,3 24,3	51,2 25,7	51,1 27,1	50,9 28,4	50,4 30,35	49,7 32,2	49 33,3	48,2 34,4	46,8 36	44 38,5	40,5 41	36* 43	31,5* 44,5		
B-N4 125-400A/A	N4 125-400A/A	250 M4	55		59,2 27,8	59,1 29,4	59 30,9	58,9 32,4	58,7 33,9	58,2 36,2	57,2 38,4	57,2 39,8	56,7 41,2	55,7 43,2	53,5 46,2	50,5 49,2	46,5* 52,1	42,5* 54,4		

PUMP B-N4	PUMP N4	MOTOR	P ₂ kW	Q m³/h	132	150	168	180	192	210	240	270	300	330	360	390	420	450	480	
				Q l/min	2200	2500	2800	3000	3200	3500	4000	4500	5000	5500	6000	6500	7000	7500	8000	
B-N4 150-315D/A	N4 150-315D/A	180 M4	18,5	H m P ₃ kW	22,8 13,8	22,6 14,5	22,3 15	22 15,4	21,7 15,75	21,1 16,2	20 16,9	18,6 17,6	17 18	15,1 18,35	13 18,45	10,6 18,4	8* 18,15			
B-N4 150-315C/A	N4 150-315C/A	180 L4	22		25,6 15,6	25,4 16,44	25,1 17,2	24,9 17,65	24,7 18,1	24,2 18,8	23,3 19,7	22 20,6	20,4 21,3	18,5 21,75	16,5 22	14,1 22	11,6* 22	8,9* 21,65		
B-N4 150-315B/A	N4 150-315B/A	200 L4	30		30,6 19	30,6 20	30,5 21	30,3 21,6	30,1 22,15	29,7 23	29 24,35	27,9 25,7	26,5 26,6	24,9 27,5	23 28,1	20,8 28,7	18,3* 28,9	15,4* 29		
B-N4 150-315A/A	N4 150-315A/A	225 S4	37		35,6 23,1	35,6 24,4	35,5 25,7	35,4 26,5	35,3 27,2	35,2 28,3	34,6 30	33,7 31,6	32,5 33,1	31 34,3	29,2 35,4	27,1 36,3	24,7* 37	21,8* 37,5	18,5* 37,8	
B-N4 150-400C/A	N4 150-400C/A	225 M4	45		45 27,9	44,9 29,65	44,7 31,4	44,5 32,6	44 33,8	43,5 35,3	42,5 37,7	40,5 39,7	38,5 41,3	36 42,7	33,5 43,8	30,5 44,1	27* 44,1	23,5* 44	19,5* 43	
B-N4 150-400B/A	N4 150-400B/A	250 M4	55		50,8 31,4	50,7 33,6	50,5 35,8	50,3 36,9	50 38,2	49,5 40,5	48,5 42,8	47 45,5	45 47,7	43 49,8	40,5 51,5	38 53	35* 54,1	32* 54,6	28,5* 54,8	
B-N4 150-400A/A	N4 150-400A/A	280 S4	75		58,8 38,2	58,7 40,7	58,6 42,8	58,5 44,35	58,3 45,7	57,9 48	57 51,5	55,5 54,4	54 57,1	52 59,7	49,5 62	47 64,2	44* 66	41* 67,5	37,5* 68,4	

N4 Standard construction.

P₂ Rated motor power output.

H Total head in m.

* Maximum suction lift 1-2 m.

B-N4 Bronze construction.













P₃ Pump power input.



End-Suction Centrifugal Pumps standardized EN 733



Characteristic curves $n \approx 2900$ rpm









End-Suction Centrifugal Pumps standardized EN 733



Characteristic curves $n \approx 2900$ rpm








End-Suction Centrifugal Pumps standardized EN 733



Characteristic curves $n \approx 2900$ rpm









End-Suction Centrifugal Pumps
standardized EN 733



Characteristic curves $n \approx 2900$ rpm








End-Suction Centrifugal Pumps standardized EN 733



Characteristic curves $n \approx 2900$ rpm











End-Suction Centrifugal Pumps standardized EN 733



Characteristic curves $n \approx 2900$ rpm



Characteristic curves $n \approx 1450$ rpm







N4





End-Suction Centrifugal Pumps
standardized EN 733



Characteristic curves $n \approx 1450$ rpm



Characteristic curves $n \approx 1450$ rpm






N4

End-Suction Centrifugal Pumps
standardized EN 733



Characteristic curves $n \approx 1450$ rpm





N4

End-Suction Centrifugal Pumps
standardized EN 733







Characteristic curves $n \approx 1450$ rpm



4

Characteristic curves $n \approx 1450$ rpm






N4

End-Suction Centrifugal Pumps
standardized EN 733

calpeda®

Characteristic curves $n \approx 1450$ rpm





N4

End-Suction Centrifugal Pumps
standardized EN 733



Characteristic curves $n \approx 1450$ rpm





N, N4


End-Suction Centrifugal Pumps
standardized EN 733

calpeda[®]

Dimensions and weights




Shaft extension ISO 775 Parallel key UNI 6604



mm			
d	l	u	t
24 j6	50	8	27
32 k6	80	10	35
42 k6	110	12	45

Flanges PN 10, EN 1092-2



mm						
DN	DG	DK	DE	Holes		W
				N°	Ø	
32	76	100	140	4	19	18
40	84	110	150	4	19	18
50	99	125	165	4	19	20
65	118	145	185	4	19	20
80	132	160	200	8	19	22
100	156	180	220	8	19	24
125	184	210	250	8	19	24
150	211	240	285	8	23	26
200	266	295	340	8	23	30

N n ≈ 2900 rpm
N4 n ≈ 1450 rpm


TYPE			mm																kg							
			DN1	DN2	a	f	h1	h2	l1	l2	m1	m2	n1	n2	b	s1	d	w	x	B-N B-N4	N N4					
B-N, B-N4 - N, N4 32-125	50	32	80	360	112	140	93	97	100	70	190	140	50	14	24	260	100	30	26,5							
B-N, B-N4 - N, N4 32-160					132	160	120	120			240	190						37	33							
B-N, B-N4 - N, N4 32-200					160	180	140	140										44	38,4							
B-N, - N, 40-125	65	40	80	360	112	140	100	113	100	70	210	160	50	14	24	260	100	32	28,4							
B-N, B-N4 - N, N4 40-160			132		160	119	119	240			190	38						33,6								
B-N, B-N4 - N, N4 40-200			100		160	180	140	140			265	212						47,1	40,4							
B-N, B-N4 - N, N4 40-250					180	225	175	175			125	95						320	250	63	55					
B-N, B-N4 - N, N4 50-125	65	50	100	360	132	160	121	137	100	70	240	190	50	14	24	260	100	42,4	36,5							
B-N, B-N4 - N, N4 50-160					160	180	127	141			265	212						45	39,2							
B-N, B-N4 - N, N4 50-200					180	200	140	153			125	95	320					250	65	54	47					
B-N, B-N4 - N, N4 50-250						225	175	175												66	57,5					
B-N, B-N4 - N, N4 65-125	80	65	100	360	160	180	134	155	125	95	280	212	65	14	24	260	100	48	42							
B-N, B-N4 - N, N4 65-160					180	200	150	172			320	250						50,6	44,5							
B-N, B-N4 - N, N4 65-200					180	225	155	175			320	250						55,5	50							
B-N, B-N4 - N, N4 65-250			125	470	200	250	175	190	160	120	360	280	80	18	32	340	140	103	90							
B-N4 - N4 65-315					225	280	220	220			400	315						149	130							
B-N, B-N4 - N, N4 80-160					100	80	125	360	180	225	165	193	125	95	320	250	65	14	24	260	140	61	53			
B-N, B-N4 - N, N4 80-200	180	250	170	194				345	280	93	80,5															
B-N, B-N4 - N, N4 80-250	470	200	280	191				210	160	120	400	315			80	18			32	340		140	110	95		
B-N4 - N4 80-315		250	315	220				232			400	315											154	134		
B-N4 - N4 80-400 (1)	125	80	125	530	280	355	268	268	160	120	435	355	80	18	42	370	140	220	192							
B-N, B-N4 - N, N4 100-200	125	100	125	470	200	280	180	212	160	120	360	280	80	18	32	340	140	103	89							
B-N, B-N4 - N, N4 100-250			140		225	250	205	233			400	315						123	104							
B-N4 - N4 100-315					250	315	230	250			400	315						158	138							
B-N4 - N4 100-400					530	280	355	268			200	150						500	400	100	22	42	370	230	200	
B-N4 - N4 125-250	150	125	140	470	250	355	235	268	160	120	400	315	80	18	32	340	140	150	129							
B-N4 - N4 125-315				530	280		247	278			200	150						500	400	100	22	42	370	140	217	189
B-N4 - N4 125-400					315		400	280																	305	255
B-N4 - N4 150-315	200	150	160	530	280	400	260	298	200	150	550	450	100	22	42	370	140	231	201							
B-N4 - N4 150-400					315	450	295	328										284	247							

1) Additional size

N End-Suction Centrifugal Pumps standardized EN 733



Dimensions



TYPE	MOTOR	kW	mm															FM≈	H≈
			DN ₁	DN ₂	a	f	h3	h2	m4	m5	w1	n4	n5	a1	g2	s1			
B-N, N 32-125	71 M2	0,55	50	32	80	360	197	140	780	750	15	240	180	90	85	14	718	308	
	80 M2	0,75	50	32	80	360	197	140	780	750	15	240	180	90	85	14	752	317	
	80 M2	1,1	50	32	80	360	197	140	780	750	15	240	180	90	85	14	752	317	
	90 S2	1,5	50	32	80	360	197	140	780	750	15	240	180	90	85	14	809	325	
B-N, N 32-160	90 S2	1,5	50	32	80	360	217	160	780	750	15	240	180	90	85	14	809	345	
	90 L2	2,2	50	32	80	360	217	160	780	750	15	240	180	90	85	14	809	345	
	100 L2	3	50	32	80	360	232	160	880	850	15	300	240	90	100	14	885	398	
B-N, N 32-200	90 L2	2,2	50	32	80	360	245	180	780	750	15	240	180	90	85	14	809	373	
	100 L2	3	50	32	80	360	260	180	880	850	15	300	240	90	100	14	885	426	
	112 M2	4	50	32	80	360	260	180	880	850	15	300	240	90	100	14	882	437	
	132 S2	5,5	50	32	80	360	260	180	1020	990	15	350	290	100	100	14	953	462	
B-N, N 40-125	80 M2	1,1	65	40	80	360	197	140	780	750	15	240	180	90	85	14	752	317	
	90 S2	1,5	65	40	80	360	197	140	780	750	15	240	180	90	85	14	809	325	
	90 L2	2,2	65	40	80	360	197	140	780	750	15	240	180	90	85	14	809	325	
B-N, N 40-160	90 L2	2,2	65	40	80	360	217	160	780	750	15	240	180	90	85	14	809	345	
	100 L2	3	65	40	80	360	232	160	880	850	15	300	240	90	100	14	885	398	
	112 M2	4	65	40	80	360	232	160	880	850	15	300	240	90	100	14	882	409	
	132 S2	5,5	65	40	80	360	232	160	1020	990	15	350	290	90	100	14	953	434	
B-N, N 40-200	112 M2	4	65	40	100	360	260	180	880	850	15	300	240	100	100	14	902	437	
	132 S2	5,5	65	40	100	360	260	180	1020	990	15	350	290	100	100	14	973	462	
	132 S2	7,5	65	40	100	360	260	180	1020	990	15	350	290	100	100	14	1023	462	
B-N, N 40-250	160 M2	11	65	40	100	360	280	225	1020	990	15	350	290	100	100	14	1082	517	
	160 M2	15	65	40	100	360	280	225	1020	990	15	350	290	100	100	14	1082	517	
B-N, N 50-125	90 L2	2,2	65	50	100	360	217	160	780	750	15	240	180	90	85	14	829	345	
	100 L2	3	65	50	100	360	232	160	880	850	15	300	240	90	100	14	905	398	
	112 M2	4	65	50	100	360	232	160	880	850	15	300	240	90	100	14	902	409	
	132 S2	5,5	65	50	100	360	232	160	1020	990	15	350	290	90	100	14	973	434	
B-N, N 50-160	132 S2	5,5	65	50	100	360	260	180	1020	990	15	350	290	100	100	14	973	462	
	132 S2	7,5	65	50	100	360	260	180	1020	990	15	350	290	100	100	14	1023	462	
B-N, N 50-200	160 M2	11	65	50	100	360	260	200	1020	990	15	350	290	100	100	14	1082	497	
	160 M2	15	65	50	100	360	260	200	1020	990	15	350	290	100	100	14	1082	497	
B-N, N 50-250	160 M2	11	65	50	100	360	280	225	1020	990	15	350	290	100	100	14	1082	517	
	160 M2	15	65	50	100	360	280	225	1020	990	15	350	290	100	100	14	1082	517	
	160 L2	18,5	65	50	100	360	280	225	1020	990	15	350	290	100	100	14	1142	517	
	180 M2	22	65	50	100	360	280	225	1140	1110	15	350	290	100	100	14	1189	566	
B-N, N 65-125	112 M2	4	80	65	100	360	260	180	880	850	15	300	240	100	100	14	902	437	
	132 S2	5,5	80	65	100	360	260	180	1020	990	15	350	290	100	100	14	973	462	
	132 S2	7,5	80	65	100	360	260	180	1020	990	15	350	290	100	100	14	1023	462	
B-N, N 65-160	132 S2	5,5	80	65	100	360	260	200	1020	990	15	350	290	100	100	14	973	462	
	132 S2	7,5	80	65	100	360	260	200	1020	990	15	350	290	100	100	14	1023	462	
	160 M2	11	80	65	100	360	260	200	1020	990	15	350	290	100	100	14	1082	497	
	160 M2	15	80	65	100	360	260	200	1020	990	15	350	290	100	100	14	1082	497	
B-N, N 65-200	160 M2	15	80	65	100	360	280	225	1020	990	15	350	290	100	100	14	1082	517	
	160 L2	18,5	80	65	100	360	280	225	1020	990	15	350	290	100	100	14	1142	517	
	180 M2	22	80	65	100	360	280	225	1140	1110	15	350	290	100	100	14	1189	566	
B-N, N 65-250	180 M2	22	80	65	100	470	310	250	1360	1320	20	400	340	130	110	18	1299	596	
	200 L2	30	80	65	100	470	310	250	1360	1320	20	400	340	130	110	18	1347	625	
	200 L2	37	80	65	100	470	310	250	1360	1320	20	400	340	130	110	18	1347	625	
B-N, N 80-160	132 S2	7,5	100	80	125	360	280	225	1020	990	15	350	290	100	100	14	1048	482	
	160 M2	11	100	80	125	360	280	225	1020	990	15	350	290	100	100	14	1107	517	
	160 M2	15	100	80	125	360	280	225	1020	990	15	350	290	100	100	14	1107	517	
	160 L2	18,5	100	80	125	360	280	225	1020	990	15	350	290	100	100	14	1167	517	
B-N, N 80-200	180 M2	22	100	80	125	470	290	250	1230	1190	20	400	340	100	110	18	1324	576	
	200 L2	30	100	80	125	470	310	250	1360	1320	20	400	340	130	110	18	1372	625	
B-N, N 80-250	180 M2	22	100	80	125	470	310	280	1360	1320	20	400	340	130	110	18	1324	596	
	200 L2	30	100	80	125	470	310	280	1360	1320	20	400	340	130	110	18	1372	625	
	200 L2	37	100	80	125	470	310	280	1360	1320	20	400	340	130	110	18	1372	625	
B-N, N 80-250	225 M2	45	100	80	125	470	385	280	1250	840	205	480	430	95	16	24	1411	723	
	250 M2	55	100	80	125	470	415	280	1250	840	205	480	430	95	16	24	1509	823	
B-N, N 100-200	160 L2	18,5	125	100	125	470	310	280	1230	1190	20	400	340	130	110	18	1263	547	
	180 M2	22	125	100	125	470	310	280	1360	1320	20	400	340	130	110	18	1324	596	
	200 L2	30	125	100	125	470	310	280	1360	1320	20	400	340	130	110	18	1372	625	
	200 L2	37	125	100	125	470	310	280	1360	1320	20	400	340	130	110	18	1372	625	
B-N, N 100-200	225 M2	45	125	100	125	470	385	280	1250	840	205	480	430	95	16	24	1411	723	
B-N, N 100-250	250 M2	55	125	100	140	470	415	280	1250	840	205	480	430	95	16	24	1524	825	
	280 S2	75	125	100	140	470	505	280	1400	940	230	510	450	95	17,5	24	1597	937	



End-Suction Centrifugal Pumps standardized EN 733



Dimensions

n ≈ 1450 rpm

TYPE	MOTOR	kW	mm															
			DN ₁	DN ₂	a	f	h3	h2	m4	m5	w1	n4	n5	a1	g2	s1	fM≈	H ≈
B-N4, N4 32-125	71 M4	0,25	50	32	80	360	197	140	780	750	15	240	180	90	85	14	718	308
B-N4, N4 32-160	71 M4	0,37	50	32	80	360	217	160	780	750	15	240	180	90	85	14	718	328
B-N4, N4 32-200	80 M4	0,55	50	32	80	360	245	180	780	750	15	240	180	90	85	14	752	365
	80 M4	0,75	50	32	80	360	245	180	780	750	15	240	180	90	85	14	752	365
B-N4, N4 40-125	71 M4	0,25	65	40	80	360	197	140	780	750	15	240	180	90	85	14	718	308
	71 M4	0,37	65	40	80	360	197	140	780	750	15	240	180	90	85	14	718	308
B-N4, N4 40-160	71 M4	0,37	65	40	80	360	217	160	780	750	15	240	180	90	85	14	718	328
	80 M4	0,55	65	40	80	360	217	160	780	750	15	240	180	90	85	14	752	337
	80 M4	0,75	65	40	80	360	217	160	780	750	15	240	180	90	85	14	752	337
B-N4, N4 40-200	90 S4	1,1	65	40	100	360	260	180	880	850	15	300	240	100	100	14	829	388
B-N4, N4 40-250	90 L4	1,5	65	40	100	360	280	225	880	850	15	350	290	100	100	14	829	408
	100 L4	2,2	65	40	100	360	280	225	880	850	15	350	290	100	100	14	905	446
	100 L4	3	65	40	100	360	280	225	880	850	15	350	290	100	100	14	905	446
B-N4, N4 50-125	71 M4	0,37	65	50	100	360	217	160	780	750	15	240	180	90	85	14	738	328
	80 M4	0,55	65	50	100	360	217	160	780	750	15	240	180	90	85	14	772	337
	80 M4	0,75	65	50	100	360	217	160	780	750	15	240	180	90	85	14	772	337
B-N4, N4 50-160	90 S4	1,1	65	50	100	360	260	180	880	850	15	300	240	100	100	14	829	388
B-N4, N4 50-200	90 S4	1,1	65	50	100	360	260	200	880	850	15	300	240	100	100	14	829	388
	90 L4	1,5	65	50	100	360	260	200	880	850	15	300	240	100	100	14	829	388
	100 L4	2,2	65	50	100	360	260	200	880	850	15	300	240	100	100	14	905	426
B-N4, N4 50-250	100 L4	2,2	65	50	100	360	280	225	880	850	15	350	290	100	100	14	905	446
	100 L4	3	65	50	100	360	280	225	880	850	15	350	290	100	100	14	905	446
	112 M4	4	65	50	100	360	280	225	880	850	15	350	290	100	100	14	902	457
B-N4, N4 65-125	80 M4	0,75	80	65	100	360	260	180	880	850	15	300	240	100	100	14	772	380
	90 S4	1,1	80	65	100	360	260	180	880	850	15	300	240	100	100	14	829	388
B-N4, N4 65-160	90 S4	1,1	80	65	100	360	260	200	880	850	15	300	240	100	100	14	829	388
	90 L4	1,5	80	65	100	360	260	200	880	850	15	300	240	100	100	14	829	388
B-N4, N4 65-200	100 L4	2,2	80	65	100	360	280	225	880	850	15	350	290	100	100	14	905	446
	100 L4	3	80	65	100	360	280	225	880	850	15	350	290	100	100	14	905	446
B-N4, N4 65-250	112 M4	4	80	65	100	470	310	250	1030	990	20	400	340	130	110	18	1012	487
	132 S4	5,5	80	65	100	470	310	250	1030	990	20	400	340	130	110	18	1055	512
B-N4, N4 65-315	132 S4	5,5	80	65	125	470	335	280	1030	990	20	400	340	130	110	18	1080	537
	132 M4	7,5	80	65	125	470	335	280	1030	990	20	400	340	130	110	18	1130	537
	160 M4	11	80	65	125	470	335	280	1230	1190	20	400	340	130	110	18	1203	572
B-N4, N4 80-160	90 S4	1,1	100	80	125	360	280	225	880	850	15	350	290	100	100	14	854	408
	90 L4	1,5	100	80	125	360	280	225	880	850	15	350	290	100	100	14	854	408
	100 L4	2,2	100	80	125	360	280	225	880	850	15	350	290	100	100	14	930	446
B-N4, N4 80-200	100 L4	2,2	100	80	125	470	280	250	1020	990	15	350	290	100	100	14	1040	446
	100 L4	3	100	80	125	470	280	250	1020	990	15	350	290	100	100	14	1040	446
	112 M4	4	100	80	125	470	280	250	1020	990	15	350	290	100	100	14	1037	457
B-N4, N4 80-250	112 M4	4	100	80	125	470	310	280	1030	990	20	400	340	130	110	18	1037	487
	132 S4	5,5	100	80	125	470	310	280	1030	990	20	400	340	130	110	18	1080	512
	132 M4	7,5	100	80	125	470	310	280	1030	990	20	400	340	130	110	18	1130	512
B-N4, N4 80-315	160 M4	11	100	80	125	470	360	315	1230	1190	20	400	340	130	110	18	1203	597
	160 L4	15	100	80	125	470	360	315	1230	1190	20	400	340	130	110	18	1263	597
B-N4, N4 80-400	180 M4	18,5	125	80	125	530	445	355	1250	840	205	480	430	115	16	24	1352	731
	180 L4	22	125	80	125	530	445	355	1250	840	205	480	430	115	16	24	1352	731
	200 L4	30	125	80	125	530	445	355	1250	840	205	480	430	110	16	24	1402	760
B-N4, N4 100-200	100 L4	3	125	100	125	470	310	280	1030	990	20	400	340	130	110	18	1040	476
	112 M4	4	125	100	125	470	310	280	1030	990	20	400	340	130	110	18	1037	487
	132 S4	5,5	125	100	125	470	310	280	1030	990	20	400	340	130	110	18	1080	512
B-N4, N4 100-250	132 M4	7,5	125	100	140	470	335	280	1030	990	20	400	340	130	110	18	1145	537
	160 M4	11	125	100	140	470	335	280	1230	1190	20	400	340	130	110	18	1218	572
B-N4, N4 100-315	160 M4	11	125	100	140	470	360	315	1230	1190	20	400	340	130	110	18	1218	597
	160 L4	15	125	100	140	470	360	315	1230	1190	20	400	340	130	110	18	1278	597
	180 M4	18,5	125	100	140	470	360	315	1360	1320	20	400	340	130	110	18	1339	646
B-N4, N4 100-400	180 L4	22	125	100	140	530	445	355	1250	840	205	480	430	115	16	24	1367	731
	200 L4	30	125	100	140	530	445	355	1250	840	205	480	430	115	16	24	1417	760
	225 S4	37	125	100	140	530	445	355	1250	840	205	480	430	115	16	24	1463	783
B-N4, N4 125-250	132 S4	5,5	150	125	140	470	360	355	1030	990	20	400	340	130	110	18	1095	562
	132 M4	7,5	150	125	140	470	360	355	1030	990	20	400	340	130	110	18	1145	562
	160 M4	11	150	125	140	470	360	355	1230	1190	20	400	340	130	110	18	1218	597
	160 L4	15	150	125	140	470	360	355	1230	1190	20	400	340	130	110	18	1278	597
B-N4, N4 125-315	180 M4	18,5	150	125	140	530	445	355	1250	840	205	480	430	115	16	24	1367	731
	180 L4	22	150	125	140	530	445	355	1250	840	205	480	430	115	16	24	1367	731
	200 L4	30	150	125	140	530	445	355	1250	840	205	480	430	115	16	24	1417	760
B-N4, N4 125-400	225 S4	37	150	125	140	530	480	400	1250	840	205	480	430	115	16	24	1463	818
	225 M4	45	150	125	140	530	480	400	1250	840	205	480	430	115	16	24	1463	818
	250 M4	55	150	125	140	530	540	400	1400	940	230	510	450	115	17,5	24	1561	950
B-N4, N4																		

Interchangeability of parts

TYPE	Bearing housing			Pump shaft					Ball bearings				Shaft sealing		
	1	2	3	I	II	III	IV	V	6207 Z 6306 Z	6207 Z 3306	6309 Z 3309	6311 Z 3311	Ø 32	Ø 40	Ø 50
N,N4 32-125	x			x					x				x		
N,N4 32-160	x				x				x				x		
N,N4 32-200	x				x				x				x		
N,N4 40-125	x				x				x				x		
N,N4 40-160	x				x				x				x		
N,N4 40-200C	x				x				x				x		
N,N4 40-200A-AR-B	x					x				x			x		
N,N4 40-250	x					x				x			x		
N,N4 50-125	x				x				x				x		
N,N4 50-160	x					x				x			x		
N,N4 50-200	x					x				x			x		
N,N4 50-250	x					x				x			x		
N 50 M	x					x				x			x		
N,N4 65-125E	x				x				x				x		
N,N4 65-125A-C	x					x				x			x		
N,N4 65-160	x					x				x			x		
N,N4 65-200	x					x				x			x		
N,N4 65-250		x					x				x			x	
N4 65-315		x					x				x			x	
N,N4 80-160	x					x				x			x		
N,N4 80-200		x					x				x			x	
N,N4 80-250		x					x				x			x	
N4 80-315		x					x				x			x	
N4 80-400			x					x				x			x
N,N4 100-200		x					x				x			x	
N,N4 100-250		x					x				x			x	
N4 100-315		x					x				x			x	
N4 100-400			x					x				x			x
N4 125-250		x					x				x			x	
N4 125-315			x					x				x			x
N4 125-400			x					x				x			x
N4 150-315			x					x				x			x
N4 150-400			x					x				x			x

Maximum permissible rotation speed


3600 rpm			3000 rpm			1800 rpm		
32-125	32-160	32-200						
40-125	40-160	40-200			40-250			
50-125	50-160	50-200			50-250			
					50 M			
65-125	65-160				65-200	65-315		
		80-200	80-160		65-250	80-315	80-400	
		100-200			80-250	100-315	100-400	
					100-250	125-250	125-315	125-400
						150-315	150-400	

Suction pipe: recommended minimum inside diameter (DN) for different capacities (Q)

Threaded pipe		G 2	G 2 1/2							
DN	mm	50	65	80	100	125	150	200	250	300
Q max	m³/h	10,5	19	28,8	45	75	108	215	350	508

Features

4



Cutting edge hydraulics

The geometry of the impeller and the pump casing are optimized to achieve maximum efficiency and the best suction capability.

Flexible

The option to choose between cast iron and bronze materials for the hydraulic parts in contact with the pumped liquid allows N-N4 series pumps to be selected for use with different types of liquids.

Robust

The mechanical structure of the hydraulic parts in contact with the pumped liquid are dimensioned to guarantee the maximum resistance to mechanical stress. Also the casing cover is provided with wings that prevent turbulence in the area of the mechanical seal, increasing the reliability.

Reliable

The bearing and shaft are designed to ensure the reduction of the stress, providing high reliability under all operating conditions.